

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015831
DATE: 07/24/2023
CERTIFICATION PROGRAM: Structural
COMPANY: Ply Gem
CODE: 1408-1

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<p>Ply Gem Window Group 433 North Main Street Rocky Mount, VA 24151</p>	<p>Series “4712FLIR & 4712FIR & 4812FIR” Aluminum Single Hung Window Configuration: O/X Glazing: IG-1/8" Annealed Glass/1/8" Annealed Glass/0.090" Eastman PVB Interlayer/1/8" Annealed Glass</p> <p>Frame: W-1346mm(53") H-1829mm(72") Sash: W-1295mm(51") H-914mm(36") DLO: W-1254mm(49.38") H-845mm(33.25")</p>

SPECIFICATION	PRODUCT RATING
<p style="text-align: center;"> AAMA 506-06/08/11/16 AAMA/WDMA/CSA 101/I.S.2/A440-17 AAMA/WDMA/CSA 101/I.S.2/A440-11 AAMA/WDMA/CSA 101/I.S.2/A440-08 AAMA/WDMA/CSA 101/I.S.2/A440-05 ASTM E1886-02/04/05/13 ASTM E1996-02/04/06/09/12/14 </p>	<p style="text-align: center;"> Class LC-PG50 1346 x 1823 (53 x 72)-H H-R50 1346 x 1823 (53 x 72) Design Pressure: ±2349 Pa (±50 psf) Positive Design Pressure: 2880 Pa (60 psf) Negative Design Pressure: 3360 Pa (70 psf) Water Penetration Resistance Test Pressure: 360 Pa (7.52 psf) ASTM Impact Rating Design Pressure: ±2349 Pa (±50 psf) Positive Design Pressure: 2349 Pa (50 psf) Negative Design Pressure: 2729 Pa (57 psf) Wind Zone 3 - Missile Level D </p>

Product Tested By: National Certified Testing Laboratories
 Report No: 110-26152-1
 Expiration Date: July 31, 2024

Administrator's Signature: _____

**NATIONAL ACCREDITATION AND
 MANAGEMENT INSTITUTE, INC.**
 4794 George Washington Memorial Highway
 Hayes, VA 23072
 Tel: (804) 684-5124
nami@namiinc.com