

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015832.16
DATE: 08/03/2023
CERTIFICATION PROGRAM: Structural
COMPANY: Ply Gem
CODE: 1408-1

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<p>Ply Gem Window Group Simonton Windows 520 Weston Parkway, Suite 300 Cary, NC 27513</p>	<p style="text-align: center;">Series “Ply Gem Perspective/ Simonton MaxView”</p> <p style="text-align: center;">Vinyl Sliding Glass Door</p> <p style="text-align: center;">(Two Track w/Interior Pocket)</p> <p style="text-align: center;">Configuration: XX-XXP Glazing: IG-3/16" Tempered Glass/1/8" Heat Strengthened Glass/0.090" Sentry Glass Interlayer/1/8" Heat Strengthened Glass</p> <p>Frame: W-5952mm(234.25") H-2426mm(95.5")</p> <p>Panel: W-1553mm(61.13") H-2364mm(93.06")</p> <p>DLO: W-1324mm(52.13") H-2135mm(84.06")</p>

SPECIFICATION	PRODUCT RATING
<p style="text-align: center;">AAMA/WDMA/CSA 101/I.S.2/A440-17 ASTM E1886-12/19 ASTM E1996-17/20</p>	<p style="text-align: center;">Class LC-PG70 6052 x 2426 (238 x 96)-SD Design Pressure: ±3360 Pa (±70 psf) Positive Design Pressure: 3360 Pa (70 psf) Negative Design Pressure: 3840 Pa (80 psf) Water Penetration Resistance Test Pressure: 510 Pa (10.66 psf) Wind Zone 3 - Missile Level D</p>

Product Tested By: Molimo Architectural Product Testing
Report No: 11835.07-106-11/W-2073
Expiration Date: **December 31, 2026**

Administrator's Signature: _____

**NATIONAL ACCREDITATION AND
MANAGEMENT INSTITUTE, INC.**
4794 George Washington Memorial Highway
Hayes, VA 23072
Tel: (804) 684-5124
Email: nami@namiinc.com