

Notice of Product Certification

CERTIFICATION NO.: 1165-004
INITIAL CERTIFICATION DATE: September 13, 2023
REVISION DATE: N/A
REPORT NUMBER: TPE22003-1-C_VSSH-2
SPECIFICATION: CSA A440.2-19

COMPANY: Portes et Fenetres Polair 3
CODE: 1165-1
EXPIRATION DATE: October 28, 2027
PRODUCT SIMULATED BY: Veridis Solutions
AIR LEAKAGE REPORT NO.: AI-04587-A1

PRODUCT/SERIES NAME: C6000 Guillotine Simple PVC-Hybride **OPERATOR TYPE:** VSSH

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
1165-004-0001-01	PVC, 3mm_7/8_PCl-arg95-8071#3, iu	0.082(#3)	1.64	0.54	0.60	0.4	34
1165-004-0002-01	PVC, 3mm_7/8_PCl-arg95-8071#3, iu, Grids<1"	0.082(#3)	1.64	0.48	0.53	0.4	31
1165-004-0003-01	PVC, 3mm_7/8_PCl-arg95-PTLX#3, iu	0.082(#3)	1.64	0.55	0.59	0.4	35
1165-004-0004-01	PVC, 3mm_7/8_PCl-arg95-PTLX#3, iu, Grids<1"	0.082(#3)	1.64	0.49	0.53	0.4	32
1165-004-0005-01	PVC, 3mm_7/8_70/36#2-arg95-PCl, iu	0.036(#2)	1.57	0.29	0.52	0.4	22
1165-004-0006-01	PVC, 3mm_7/8_70/36#2-arg95-PCl, iu, Grids<1"	0.036(#2)	1.57	0.26	0.46	0.4	20
1165-004-0007-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCl-arg95-PCl, iu	0.036(#2)	1.33	0.27	0.48	0.4	26
1165-004-0008-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCl-arg95-PCl, iu, Grids<1"	0.036(#2)	1.33	0.24	0.43	0.4	24
1165-004-0009-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCl-arg95-70/36#5, iu	0.036(#2) 0.036(#5)	1.10	0.25	0.41	0.4	30
1165-004-0010-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCl-arg95-70/36#5, iu, Grids<1"	0.036(#2) 0.036(#5)	1.10	0.22	0.36	0.4	28
1165-004-0011-01	PVC, 3mm_1 1/8_80/71#2-arg95-PCl-arg95-80/71#5, iu	0.082(#2) 0.082(#5)	1.15	0.44	0.53	0.4	39
1165-004-0012-01	PVC, 3mm_1 1/8_80/71#2-arg95-PCl-arg95-80/71#5, iu, Grids<1"	0.082(#2) 0.082(#5)	1.15	0.39	0.47	0.4	37
1165-004-0013-01	PVC, 3mm_1 1/8_PCl-arg95-PCl-arg95-80/71#5, iu	0.082(#5)	1.36	0.49	0.55	0.4	38
1165-004-0014-01	PVC, 3mm_1 1/8_PCl-arg95-PCl-arg95-80/71#5, iu, Grids<1"	0.082(#5)	1.36	0.44	0.49	0.4	35
1165-004-0015-01	PVC, 3mm_7/8_PCl-arg95-8071#3, ms	0.082(#3)	1.65	0.54	0.60	0.4	34
1165-004-0016-01	PVC, 3mm_7/8_PCl-arg95-8071#3, ms, Grids<1"	0.082(#3)	1.65	0.48	0.53	0.4	31
1165-004-0017-01	PVC, 3mm_7/8_PCl-arg95-PTLX#3, ms	0.082(#3)	1.65	0.55	0.59	0.4	35
1165-004-0018-01	PVC, 3mm_7/8_PCl-arg95-PTLX#3, ms, Grids<1"	0.082(#3)	1.65	0.49	0.53	0.4	31
1165-004-0019-01	PVC, 3mm_7/8_70/36#2-arg95-PCl, ms	0.036(#2)	1.57	0.29	0.52	0.4	22
1165-004-0020-01	PVC, 3mm_7/8_70/36#2-arg95-PCl, ms, Grids<1"	0.036(#2)	1.57	0.26	0.46	0.4	20
1165-004-0021-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCl-arg95-PCl, ms	0.036(#2)	1.35	0.27	0.48	0.4	25
1165-004-0022-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCl-arg95-PCl, ms, Grids<1"	0.036(#2)	1.35	0.24	0.43	0.4	24
1165-004-0023-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCl-arg95-70/36#5, ms	0.036(#2) 0.036(#5)	1.12	0.25	0.41	0.4	29
1165-004-0024-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCl-arg95-70/36#5, ms, Grids<1"	0.036(#2) 0.036(#5)	1.12	0.22	0.36	0.4	27
1165-004-0025-01	PVC, 3mm_1 1/8_80/71#2-arg95-PCl-arg95-80/71#5, ms	0.082(#2) 0.082(#5)	1.17	0.44	0.53	0.4	39

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
1165-004-0026-01	PVC, 3mm_1 1/8_80/71#2-arg95-PCI-arg95-80/71#5, ms, Grids<1"	0.082(#2) 0.082(#5)	1.17	0.39	0.47	0.4	36
1165-004-0027-01	PVC, 3mm_1 1/8_PCI-arg95-PCI-arg95-80/71#5, ms	0.082(#5)	1.38	0.49	0.55	0.4	37
1165-004-0028-01	PVC, 3mm_1 1/8_PCI-arg95-PCI-arg95-80/71#5, ms, Grids<1"	0.082(#5)	1.38	0.44	0.49	0.4	34
1165-004-0029-01	PVC, 3mm_7/8_PCI-arg95-8071#3, sw	0.082(#3)	1.60	0.54	0.60	0.4	35
1165-004-0030-01	PVC, 3mm_7/8_PCI-arg95-8071#3, sw, Grids<1"	0.082(#3)	1.60	0.48	0.53	0.4	32
1165-004-0031-01	PVC, 3mm_7/8_PCI-arg95-PTLX#3, sw	0.082(#3)	1.60	0.55	0.59	0.4	36
1165-004-0032-01	PVC, 3mm_7/8_PCI-arg95-PTLX#3, sw, Grids<1"	0.082(#3)	1.60	0.49	0.53	0.4	32
1165-004-0033-01	PVC, 3mm_7/8_70/36#2-arg95-PCI, sw	0.036(#2)	1.53	0.29	0.52	0.4	22
1165-004-0034-01	PVC, 3mm_7/8_70/36#2-arg95-PCI, sw, Grids<1"	0.036(#2)	1.53	0.26	0.46	0.4	21
1165-004-0035-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-PCI, sw	0.036(#2)	1.30	0.27	0.48	0.4	26
1165-004-0036-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-PCI, sw, Grids<1"	0.036(#2)	1.30	0.24	0.43	0.4	25
1165-004-0037-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-70/36#5, sw	0.036(#2) 0.036(#5)	1.06	0.25	0.41	0.4	30
1165-004-0038-01	PVC, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-70/36#5, sw, Grids<1"	0.036(#2) 0.036(#5)	1.06	0.22	0.36	0.4	29
1165-004-0039-01	PVC, 3mm_1 1/8_80/71#2-arg95-PCI-arg95-80/71#5, sw	0.082(#2) 0.082(#5)	1.11	0.44	0.53	0.4	40
1165-004-0040-01	PVC, 3mm_1 1/8_80/71#2-arg95-PCI-arg95-80/71#5, sw, Grids<1"	0.082(#2) 0.082(#5)	1.11	0.39	0.47	0.4	37
1165-004-0041-01	PVC, 3mm_1 1/8_PCI-arg95-PCI-arg95-80/71#5, sw	0.082(#5)	1.32	0.49	0.55	0.4	39
1165-004-0042-01	PVC, 3mm_1 1/8_PCI-arg95-PCI-arg95-80/71#5, sw, Grids<1"	0.082(#5)	1.32	0.44	0.49	0.4	36
1165-004-0043-01	PVC, 3mm_1 1/8_PTLX#2-arg95-PCI-arg95-PTLX#5, sw	0.082(#2) 0.082(#5)	1.11	0.45	0.52	0.4	41
1165-004-0044-01	PVC, 3mm_1 1/8_PTLX#2-arg95-PCI-arg95-PTLX#5, sw,Grids<1"	0.082(#2) 0.082(#5)	1.11	0.40	0.46	0.4	38
1165-004-0045-01	PVC, 3mm_1 1/8_PCI-arg95-PCI-arg95-PTLX#5, sw	0.082(#5)	1.32	0.50	0.54	0.4	39
1165-004-0046-01	PVC, 3mm_1 1/8_PCI-arg95-PCI-arg95-PTLX#5, sw,Grids<1"	0.082(#5)	1.32	0.45	0.48	0.4	36
1165-004-0047-01	HYB, 3mm_7/8_PCI-arg95-8071#3, iu	0.082(#3)	1.64	0.54	0.60	0.4	34
1165-004-0048-01	HYB, 3mm_7/8_PCI-arg95-8071#3, iu,Grids<1"	0.082(#3)	1.64	0.48	0.53	0.4	31
1165-004-0049-01	HYB, 3mm_7/8_PCI-arg95-PTLX#3, iu	0.082(#3)	1.64	0.55	0.59	0.4	35
1165-004-0050-01	HYB, 3mm_7/8_PCI-arg95-PTLX#3, iu,Grids<1"	0.082(#3)	1.64	0.49	0.53	0.4	32
1165-004-0051-01	HYB, 3mm_7/8_70/36#2-arg95-PCI, iu	0.036(#2)	1.57	0.29	0.52	0.4	22
1165-004-0052-01	HYB, 3mm_7/8_70/36#2-arg95-PCI, iu,Grids<1"	0.036(#2)	1.57	0.26	0.46	0.4	20
1165-004-0053-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-PCI, iu	0.036(#2)	1.33	0.27	0.48	0.4	26
1165-004-0054-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-PCI, iu,Grids<1"	0.036(#2)	1.33	0.24	0.43	0.4	24
1165-004-0055-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-70/36#5, iu	0.036(#2) 0.036(#5)	1.10	0.25	0.41	0.4	30
1165-004-0056-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-70/36#5, iu,Grids<1"	0.036(#2) 0.036(#5)	1.10	0.22	0.36	0.4	28
1165-004-0057-01	HYB, 3mm_1 1/8_80/71#2-arg95-PCI-arg95-80/71#5, iu	0.082(#2) 0.082(#5)	1.15	0.44	0.53	0.4	39
1165-004-0058-01	HYB, 3mm_1 1/8_80/71#2-arg95-PCI-arg95-80/71#5, iu,Grids<1"	0.082(#2) 0.082(#5)	1.15	0.39	0.47	0.4	37
1165-004-0059-01	HYB, 3mm_1 1/8_PCI-arg95-PCI-arg95-80/71#5, iu	0.082(#5)	1.36	0.49	0.55	0.4	38
1165-004-0060-01	HYB, 3mm_1 1/8_PCI-arg95-PCI-arg95-80/71#5, iu,Grids<1"	0.082(#5)	1.36	0.44	0.49	0.4	35
1165-004-0061-01	HYB, 3mm_7/8_PCI-arg95-8071#3, ms	0.082(#3)	1.65	0.54	0.60	0.4	34
1165-004-0062-01	HYB, 3mm_7/8_PCI-arg95-8071#3, ms,Grids<1"	0.082(#3)	1.65	0.48	0.53	0.4	31
1165-004-0063-01	HYB, 3mm_7/8_PCI-arg95-PTLX#3, ms	0.082(#3)	1.65	0.55	0.59	0.4	35
1165-004-0064-01	HYB, 3mm_7/8_PCI-arg95-PTLX#3, ms,Grids<1"	0.082(#3)	1.65	0.49	0.53	0.4	31
1165-004-0065-01	HYB, 3mm_7/8_70/36#2-arg95-PCI, ms	0.036(#2)	1.57	0.29	0.52	0.4	22

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
1165-004-0066-01	HYB, 3mm_7/8_70/36#2-arg95-PCI, ms,Grids<1"	0.036(#2)	1.57	0.26	0.46	0.4	20
1165-004-0067-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-PCI, ms	0.036(#2)	1.35	0.27	0.48	0.4	25
1165-004-0068-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-PCI, ms,Grids<1"	0.036(#2)	1.35	0.24	0.43	0.4	24
1165-004-0069-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-70/36#5, ms	0.036(#2) 0.036(#5)	1.12	0.25	0.41	0.4	29
1165-004-0070-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-70/36#5, ms,Grids<1"	0.036(#2) 0.036(#5)	1.12	0.22	0.36	0.4	27
1165-004-0071-01	HYB, 3mm_1 1/8_80/71#2-arg95-PCI-arg95-80/71#5, ms	0.082(#2) 0.082(#5)	1.17	0.44	0.53	0.4	39
1165-004-0072-01	HYB, 3mm_1 1/8_80/71#2-arg95-PCI-arg95-80/71#5, ms,Grids<1"	0.082(#2) 0.082(#5)	1.17	0.39	0.47	0.4	36
1165-004-0073-01	HYB, 3mm_1 1/8_PCI-arg95-PCI-arg95-80/71#5, ms	0.082(#5)	1.38	0.49	0.55	0.4	37
1165-004-0074-01	HYB, 3mm_1 1/8_PCI-arg95-PCI-arg95-80/71#5, ms,Grids<1"	0.082(#5)	1.38	0.44	0.49	0.4	34
1165-004-0075-01	HYB, 3mm_7/8_PCI-arg95-8071#3, sw	0.082(#3)	1.60	0.54	0.60	0.4	35
1165-004-0076-01	HYB, 3mm_7/8_PCI-arg95-8071#3, sw,Grids<1"	0.082(#3)	1.60	0.48	0.53	0.4	32
1165-004-0077-01	HYB, 3mm_7/8_PCI-arg95-PTLX#3, sw	0.082(#3)	1.60	0.55	0.59	0.4	36
1165-004-0078-01	HYB, 3mm_7/8_PCI-arg95-PTLX#3, sw,Grids<1"	0.082(#3)	1.60	0.49	0.53	0.4	32
1165-004-0079-01	HYB, 3mm_7/8_70/36#2-arg95-PCI, sw	0.036(#2)	1.53	0.29	0.52	0.4	22
1165-004-0080-01	HYB, 3mm_7/8_70/36#2-arg95-PCI, sw,Grids<1"	0.036(#2)	1.53	0.26	0.46	0.4	21
1165-004-0081-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-PCI, sw	0.036(#2)	1.30	0.27	0.48	0.4	26
1165-004-0082-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-PCI, sw,Grids<1"	0.036(#2)	1.30	0.24	0.43	0.4	25
1165-004-0083-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-70/36#5, sw	0.036(#2) 0.036(#5)	1.06	0.25	0.41	0.4	30
1165-004-0084-01	HYB, 3mm_1 1/8_70/36#2-arg95-PCI-arg95-70/36#5, sw,Grids<1"	0.036(#2) 0.036(#5)	1.06	0.22	0.36	0.4	29
1165-004-0085-01	HYB, 3mm_1 1/8_80/71#2-arg95-PCI-arg95-80/71#5, sw	0.082(#2) 0.082(#5)	1.11	0.44	0.53	0.4	40
1165-004-0086-01	HYB, 3mm_1 1/8_80/71#2-arg95-PCI-arg95-80/71#5, sw,Grids<1"	0.082(#2) 0.082(#5)	1.11	0.39	0.47	0.4	37
1165-004-0087-01	HYB, 3mm_1 1/8_PCI-arg95-PCI-arg95-80/71#5, sw	0.082(#5)	1.32	0.49	0.55	0.4	39
1165-004-0088-01	HYB, 3mm_1 1/8_PCI-arg95-PCI-arg95-80/71#5, sw,Grids<1"	0.082(#5)	1.32	0.44	0.49	0.4	36
1165-004-0089-01	HYB, 3mm_1 1/8_PTLX#2-arg95-PCI-arg95-PTLX#5, sw	0.082(#2) 0.082(#5)	1.11	0.45	0.52	0.4	41
1165-004-0090-01	HYB, 3mm_1 1/8_PTLX#2-arg95-PCI-arg95-PTLX#5, sw,Grids<1"	0.082(#2) 0.082(#5)	1.11	0.40	0.46	0.4	38
1165-004-0091-01	HYB, 3mm_1 1/8_PCI-arg95-PCI-arg95-PTLX#5, sw	0.082(#5)	1.32	0.50	0.54	0.4	39
1165-004-0092-01	HYB, 3mm_1 1/8_PCI-arg95-PCI-arg95-PTLX#5, sw,Grids<1"	0.082(#5)	1.32	0.45	0.48	0.4	36

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

A handwritten signature in black ink, appearing to be "S. D.".

National Accreditation & Management Institute, Inc.
 4794 George Washington Memorial Hwy.
 Hayes, VA 23072
 Tel.: (804) 684-5124
 nami@namiinc.com
 namicertification.com