

Notice of Product Certification

CERTIFICATION NO.: 2941-003
INITIAL CERTIFICATION DATE: September 6, 2023
REVISION DATE: N/A
REPORT NUMBER: TPE22009-10-C_CSSV
SPECIFICATION: CSA A440.2-22

COMPANY: NORDSTAR
CODE: 2941-1
EXPIRATION DATE: November 22, 2027
PRODUCT SIMULATED BY: Veridis Solutions
AIR LEAKAGE REPORT NO.: AI-04196-B1

PRODUCT/SERIES NAME: B4000-B3000G PVC&HYB (CAS) **OPERATOR TYPE:** CSSV

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2941-003-0001-01	PVC_3mm_7/8_GCl-arg95-8071, ms	0.082(#3)	1.53	0.46	0.52	0.0	33
2941-003-0002-01	PVC_3mm_7/8_GCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.53	0.42	0.47	0.0	31
2941-003-0003-01	PVC_3mm_7/8_GCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.53	0.38	0.42	0.0	28
2941-003-0004-01	PVC_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms	0.082(#5)	1.23	0.42	0.48	0.0	37
2941-003-0005-01	PVC_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms, Grids<1"	0.082(#5)	1.23	0.38	0.43	0.0	35
2941-003-0006-01	PVC_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms, Grids>1"	0.082(#5)	1.23	0.34	0.38	0.0	33
2941-003-0007-01	PVC_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms	0.082(#2, #5)	1.04	0.38	0.46	0.0	39
2941-003-0008-01	PVC_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms, Grids<1"	0.082(#2, #5)	1.04	0.35	0.42	0.0	37
2941-003-0009-01	PVC_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms, Grids>1"	0.082(#2, #5)	1.04	0.31	0.38	0.0	35
2941-003-0010-01	PVC_3mm_7/8_GCl-arg95-8071, sp	0.082(#3)	1.49	0.46	0.52	0.0	34
2941-003-0011-01	PVC_3mm_7/8_GCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.49	0.42	0.47	0.0	32
2941-003-0012-01	PVC_3mm_7/8_GCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.49	0.38	0.42	0.0	29
2941-003-0013-01	HYB_3mm_7/8_GCl-arg95-8071, ms	0.082(#3)	1.53	0.46	0.52	0.0	33
2941-003-0014-01	HYB_3mm_7/8_GCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.53	0.42	0.47	0.0	31
2941-003-0015-01	HYB_3mm_7/8_GCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.53	0.38	0.42	0.0	28
2941-003-0016-01	HYB_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms	0.082(#5)	1.23	0.42	0.48	0.0	37
2941-003-0017-01	HYB_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms, Grids<1"	0.082(#5)	1.23	0.38	0.43	0.0	35
2941-003-0018-01	HYB_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms, Grids>1"	0.082(#5)	1.23	0.34	0.38	0.0	33
2941-003-0019-01	HYB_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms	0.082(#2, #5)	1.04	0.38	0.46	0.0	39
2941-003-0020-01	HYB_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms, Grids<1"	0.082(#2, #5)	1.04	0.35	0.42	0.0	37
2941-003-0021-01	HYB_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms, Grids>1"	0.082(#2, #5)	1.04	0.31	0.38	0.0	35
2941-003-0022-01	HYB_3mm_7/8_GCl-arg95-8071, sp	0.082(#3)	1.49	0.46	0.52	0.0	34

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2941-003-0023-01	HYB_3mm_7/8_GCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.49	0.42	0.47	0.0	32
2941-003-0024-01	HYB_3mm_7/8_GCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.49	0.38	0.42	0.0	29

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

A handwritten signature in black ink, appearing to be 'S. D.', written over a horizontal line.

National Accreditation & Management Institute, Inc.
 4794 George Washington Memorial Hwy.
 Hayes, VA 23072
 Tel.: (804) 684-5124
 nami@namiinc.com
 namicertification.com