

Notice of Product Certification

CERTIFICATION NO.: 2941-005
INITIAL CERTIFICATION DATE: September 6, 2023
REVISION DATE: N/A
REPORT NUMBER: TPE22005-3-C_HSOX
SPECIFICATION: CSA A440.2-22

COMPANY: NORDSTAR
CODE: 2941-1
EXPIRATION DATE: October 11, 2027
PRODUCT SIMULATED BY: Veridis Solutions
AIR LEAKAGE REPORT NO.: AI-04331-A1

PRODUCT/SERIES NAME: Coulissant Simple C2000 **OPERATOR TYPE:** HSOX

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2941-005-0001-01	PVC_3mm_7/8_GCl-arg95-8071, ms	0.082(#3)	1.62	0.52	0.58	0.2	34
2941-005-0002-01	PVC_3mm_7/8_GCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.62	0.46	0.52	0.2	31
2941-005-0003-01	PVC_3mm_7/8_GCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.62	0.41	0.45	0.2	28
2941-005-0004-01	PVC_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms	0.082(#5)	1.29	0.47	0.53	0.2	39
2941-005-0005-01	PVC_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms, Grids<1"	0.082(#5)	1.29	0.42	0.47	0.2	36
2941-005-0006-01	PVC_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms, Grids>1"	0.082(#5)	1.29	0.37	0.41	0.2	33
2941-005-0007-01	PVC_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms	0.082(#2, #5)	1.08	0.43	0.52	0.2	41
2941-005-0008-01	PVC_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms, Grids<1"	0.082(#2, #5)	1.08	0.38	0.46	0.2	38
2941-005-0009-01	PVC_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms, Grids>1"	0.082(#2, #5)	1.08	0.34	0.40	0.2	36
2941-005-0010-01	PVC_3mm_7/8_GCl-arg95-8071, sp	0.082(#3)	1.58	0.52	0.58	0.2	35
2941-005-0011-01	PVC_3mm_7/8_GCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.58	0.46	0.52	0.2	32
2941-005-0012-01	PVC_3mm_7/8_GCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.58	0.41	0.45	0.2	29
2941-005-0013-01	HYB_3mm_7/8_GCl-arg95-8071, ms	0.082(#3)	1.62	0.52	0.58	0.2	34
2941-005-0014-01	HYB_3mm_7/8_GCl-arg95-8071, ms, Grids<1"	0.082(#3)	1.62	0.46	0.52	0.2	31
2941-005-0015-01	HYB_3mm_7/8_GCl-arg95-8071, ms, Grids>1"	0.082(#3)	1.62	0.41	0.45	0.2	28
2941-005-0016-01	HYB_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms	0.082(#5)	1.29	0.47	0.53	0.2	39
2941-005-0017-01	HYB_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms, Grids<1"	0.082(#5)	1.29	0.42	0.47	0.2	36
2941-005-0018-01	HYB_3mm_1 1/4_GCl-arg95-GCl-arg95-8071, ms, Grids>1"	0.082(#5)	1.29	0.37	0.41	0.2	33
2941-005-0019-01	HYB_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms	0.082(#2, #5)	1.08	0.43	0.52	0.2	41
2941-005-0020-01	HYB_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms, Grids<1"	0.082(#2, #5)	1.08	0.38	0.46	0.2	38
2941-005-0021-01	HYB_3mm_1 1/4_8071-arg95-GCl-arg95-8071, ms, Grids>1"	0.082(#2, #5)	1.08	0.34	0.40	0.2	36
2941-005-0022-01	HYB_3mm_7/8_GCl-arg95-8071, sp	0.082(#3)	1.58	0.52	0.58	0.2	35

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
2941-005-0023-01	HYB_3mm_7/8_GCl-arg95-8071, sp, Grids<1"	0.082(#3)	1.58	0.46	0.52	0.2	32
2941-005-0024-01	HYB_3mm_7/8_GCl-arg95-8071, sp, Grids>1"	0.082(#3)	1.58	0.41	0.45	0.2	29

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

National Accreditation & Management Institute, Inc.
 4794 George Washington Memorial Hwy.
 Hayes, VA 23072
 Tel.: (804) 684-5124
 nami@namiinc.com
 namicertification.com