

Notice of Product Certification

CERTIFICATION NO.: 815-003

COMPANY: Extreme Window & Entrance Systems

INITIAL CERTIFICATION DATE: September 12, 2023

CODE: 815-1

REVISION DATE: N/A

EXPIRATION DATE: August 1, 2028

REPORT NUMBER: TPE23008-6-C_CSSV-a-4

PRODUCT SIMULATED BY: Veridis Solutions

SPECIFICATION: CSA A440.2-22

AIR LEAKAGE REPORT NO.: AI-03430-C3

PRODUCT/SERIES NAME: Advantage Casement Heritage + Premium OPERATOR TYPE: CSSV

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
815-003-0001-01	3mm, 7-8, CG70#2-arg95-GCl, se	0.025(#2)	1.43	0.23	0.45	0.1	22
815-003-0002-01	3mm, 7-8, CG70#2-arg95-GCl, se, Grids< 1"	0.025(#2)	1.43	0.21	0.41	0.1	21
815-003-0003-01	3mm, 7-8, CG70#2-arg95-GCl, se, Grids>= 1"	0.025(#2)	1.43	0.19	0.36	0.1	19
815-003-0004-01	3mm, 7-8, CG70#2-arg95-GCl, se, SDL< 1"	0.025(#2)	1.43	0.21	0.41	0.1	21
815-003-0005-01	3mm, 7-8, CG70#2-arg95-GCl, se, SDL>= 1"	0.025(#2)	1.43	0.19	0.36	0.1	19
815-003-0006-01	3mm, 7-8, GCl-arg95-8071#3, se	0.082(#3)	1.52	0.47	0.52	0.1	34
815-003-0007-01	3mm, 7-8, GCl-arg95-8071#3, se, Grids< 1"	0.082(#3)	1.52	0.42	0.47	0.1	31
815-003-0008-01	3mm, 7-8, GCl-arg95-8071#3, se, Grids>= 1"	0.082(#3)	1.52	0.38	0.42	0.1	28
815-003-0009-01	3mm, 7-8, GCl-arg95-8071#3, se, SDL< 1"	0.082(#3)	1.52	0.42	0.47	0.1	31
815-003-0010-01	3mm, 7-8, GCl-arg95-8071#3, se, SDL>= 1"	0.082(#3)	1.52	0.38	0.42	0.1	28
815-003-0011-01	3mm, 1 1-4, 8071#2-arg95-GCl-arg95-8071#5, se	0.082(#2) 0.082(#5)	1.02	0.38	0.47	0.1	39
815-003-0012-01	3mm, 1 1-4, 8071#2-arg95-GCl-arg95-8071#5, se, Grids< 1"	0.082(#2) 0.082(#5)	1.02	0.35	0.42	0.1	38
815-003-0013-01	3mm, 1 1-4, 8071#2-arg95-GCl-arg95-8071#5, se, Grids>= 1"	0.082(#2) 0.082(#5)	1.02	0.32	0.38	0.1	36
815-003-0014-01	3mm, 1 1-4, 8071#2-arg95-GCl-arg95-8071#5, se, SDL< 1"	0.082(#2) 0.082(#5)	1.02	0.35	0.42	0.1	38
815-003-0015-01	3mm, 1 1-4, 8071#2-arg95-GCl-arg95-8071#5, se, SDL>= 1"	0.082(#2) 0.082(#5)	1.02	0.32	0.38	0.1	36
815-003-0016-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-CG70#5, se	0.025(#2) 0.025(#5)	0.96	0.19	0.34	0.1	30
815-003-0017-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-CG70#5, se, Grids< 1"	0.025(#2) 0.025(#5)	0.96	0.17	0.31	0.1	29
815-003-0018-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-CG70#5, se, Grids>= 1"	0.025(#2) 0.025(#5)	0.96	0.16	0.28	0.1	28
815-003-0019-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-CG70#5, se, SDL< 1"	0.025(#2) 0.025(#5)	0.96	0.17	0.31	0.1	29
815-003-0020-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-CG70#5, se, SDL>= 1"	0.025(#2) 0.025(#5)	0.96	0.16	0.28	0.1	28
815-003-0021-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-GCl, se	0.025(#2)	1.18	0.21	0.41	0.1	26
815-003-0022-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-GCl, se, Grids< 1"	0.025(#2)	1.18	0.20	0.37	0.1	26
815-003-0023-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-GCl, se, Grids>= 1"	0.025(#2)	1.18	0.18	0.33	0.1	24
815-003-0024-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-GCl, se, SDL< 1"	0.025(#2)	1.18	0.20	0.37	0.1	26
815-003-0025-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-GCl, se, SDL>= 1"	0.025(#2)	1.18	0.18	0.33	0.1	24

Product Number	Manufacturer Product Code	Emissivity (Surface #)	U-Factor (Metric)	SHGC(w)	Visible Transmittance (VT)	Air Leakage Average (L75)	Energy Rating
815-003-0026-01	3mm, 1 1-4, GCl-arg95-GCl-arg95-8071#5, se	0.082(#5)	1.21	0.42	0.48	0.1	38
815-003-0027-01	3mm, 1 1-4, GCl-arg95-GCl-arg95-8071#5, se, Grids< 1"	0.082(#5)	1.21	0.38	0.43	0.1	35
815-003-0028-01	3mm, 1 1-4, GCl-arg95-GCl-arg95-8071#5, se, Grids>= 1"	0.082(#5)	1.21	0.34	0.39	0.1	33
815-003-0029-01	3mm, 1 1-4, GCl-arg95-GCl-arg95-8071#5, se, SDL< 1"	0.082(#5)	1.21	0.38	0.43	0.1	35
815-003-0030-01	3mm, 1 1-4, GCl-arg95-GCl-arg95-8071#5, se, SDL>= 1"	0.082(#5)	1.21	0.34	0.39	0.1	33
815-003-0031-01	3mm, 7-8, CG70#2-arg95-GCl, ss	0.025(#2)	1.43	0.23	0.45	0.1	22
815-003-0032-01	3mm, 7-8, CG70#2-arg95-GCl, ss, Grids< 1"	0.025(#2)	1.43	0.21	0.41	0.1	21
815-003-0033-01	3mm, 7-8, CG70#2-arg95-GCl, ss, Grids>= 1"	0.025(#2)	1.43	0.19	0.36	0.1	19
815-003-0034-01	3mm, 7-8, CG70#2-arg95-GCl, ss, SDL< 1"	0.025(#2)	1.43	0.21	0.41	0.1	21
815-003-0035-01	3mm, 7-8, CG70#2-arg95-GCl, ss, SDL>= 1"	0.025(#2)	1.43	0.19	0.36	0.1	19
815-003-0036-01	3mm, 7-8, GCl-arg95-8071#3, ss	0.082(#3)	1.51	0.47	0.52	0.1	34
815-003-0037-01	3mm, 7-8, GCl-arg95-8071#3, ss, Grids< 1"	0.082(#3)	1.51	0.42	0.47	0.1	31
815-003-0038-01	3mm, 7-8, GCl-arg95-8071#3, ss, Grids>= 1"	0.082(#3)	1.51	0.38	0.42	0.1	29
815-003-0039-01	3mm, 7-8, GCl-arg95-8071#3, ss, SDL< 1"	0.082(#3)	1.51	0.42	0.47	0.1	31
815-003-0040-01	3mm, 7-8, GCl-arg95-8071#3, ss, SDL>= 1"	0.082(#3)	1.51	0.38	0.42	0.1	29
815-003-0041-01	3mm, 1 1-4, 8071#2-arg95-GCl-arg95-8071#5, ss	0.082(#2) 0.082(#5)	1.01	0.38	0.47	0.1	40
815-003-0042-01	3mm, 1 1-4, 8071#2-arg95-GCl-arg95-8071#5, ss, Grids< 1"	0.082(#2) 0.082(#5)	1.01	0.35	0.42	0.1	38
815-003-0043-01	3mm, 1 1-4, 8071#2-arg95-GCl-arg95-8071#5, ss, Grids>= 1"	0.082(#2) 0.082(#5)	1.01	0.32	0.38	0.1	36
815-003-0044-01	3mm, 1 1-4, 8071#2-arg95-GCl-arg95-8071#5, ss, SDL< 1"	0.082(#2) 0.082(#5)	1.01	0.35	0.42	0.1	38
815-003-0045-01	3mm, 1 1-4, 8071#2-arg95-GCl-arg95-8071#5, ss, SDL>= 1"	0.082(#2) 0.082(#5)	1.01	0.32	0.38	0.1	36
815-003-0046-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-CG70#5, ss	0.025(#2) 0.025(#5)	0.95	0.19	0.34	0.1	30
815-003-0047-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-CG70#5, ss, Grids< 1"	0.025(#2) 0.025(#5)	0.95	0.17	0.31	0.1	29
815-003-0048-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-CG70#5, ss, Grids>= 1"	0.025(#2) 0.025(#5)	0.95	0.16	0.28	0.1	28
815-003-0049-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-CG70#5, ss, SDL< 1"	0.025(#2) 0.025(#5)	0.95	0.17	0.31	0.1	29
815-003-0050-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-CG70#5, ss, SDL>= 1"	0.025(#2) 0.025(#5)	0.95	0.16	0.28	0.1	28
815-003-0051-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-GCl, ss	0.025(#2)	1.17	0.21	0.41	0.1	26
815-003-0052-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-GCl, ss, Grids< 1"	0.025(#2)	1.17	0.19	0.37	0.1	25
815-003-0053-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-GCl, ss, Grids>= 1"	0.025(#2)	1.17	0.18	0.33	0.1	25
815-003-0054-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-GCl, ss, SDL< 1"	0.025(#2)	1.17	0.19	0.37	0.1	25
815-003-0055-01	3mm, 1 1-4, CG70#2-arg95-GCl-arg95-GCl, ss, SDL>= 1"	0.025(#2)	1.17	0.18	0.33	0.1	25
815-003-0056-01	3mm, 1 1-4, GCl-arg95-GCl-arg95-8071#5, ss	0.082(#5)	1.20	0.42	0.48	0.1	38
815-003-0057-01	3mm, 1 1-4, GCl-arg95-GCl-arg95-8071#5, ss, Grids< 1"	0.082(#5)	1.20	0.38	0.43	0.1	35
815-003-0058-01	3mm, 1 1-4, GCl-arg95-GCl-arg95-8071#5, ss, Grids>= 1"	0.082(#5)	1.20	0.34	0.39	0.1	33
815-003-0059-01	3mm, 1 1-4, GCl-arg95-GCl-arg95-8071#5, ss, SDL< 1"	0.082(#5)	1.20	0.38	0.43	0.1	35
815-003-0060-01	3mm, 1 1-4, GCl-arg95-GCl-arg95-8071#5, ss, SDL>= 1"	0.082(#5)	1.20	0.34	0.39	0.1	33
815-003-0061-01	3mm, 1 1-4, GCl-arg95-8071#3-arg95-8071#5, se	0.082(#3) 0.082(#5)	1.02	0.40	0.47	0.1	41
815-003-0062-01	3mm, 1 1-4, GCl-arg95-8071#3-arg95-8071#5, se, Grids<1"	0.082(#3) 0.082(#5)	1.02	0.37	0.42	0.1	39
815-003-0063-01	3mm, 1 1-4, GCl-arg95-8071#3-arg95-8071#5, se, Grids>1"	0.082(#3) 0.082(#5)	1.02	0.33	0.38	0.1	37
815-003-0064-01	3mm, 1 1-4, GCl-arg95-8071#3-arg95-8071#5, se, SDL<1"	0.082(#3) 0.082(#5)	1.02	0.37	0.42	0.1	39
815-003-0065-01	3mm, 1 1-4, GCl-arg95-8071#3-arg95-8071#5, se, SDL>1"	0.082(#3) 0.082(#5)	1.02	0.33	0.38	0.1	37

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).



Administrator's Signature:

A handwritten signature in black ink, appearing to be "S. D.", written over a horizontal line.

National Accreditation & Management Institute, Inc.
4794 George Washington Memorial Hwy.
Hayes, VA 23072
Tel.: (804) 684-5124
nami@namiinc.com
namicertification.com