NOTICE OF PRODUCT CERTIFICATION



This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION |
|----------------------------|---|
| Monterey Bay Door, Inc. | 20 Minute Fiberglass Reinforced Faced |
| 755 Vertin Avenue, Suite F | Door w/Proprietary Core |
| Salinas, CA 93901 | (Simulated Panel Type or Flush) |
| | Manufacture Specific Fire Door Frames for Single Swing Installation in 20 Minute Locations |
| | Single Door Maximum Size: 3'0" x 8'0" |
| | Minimum Thickness: 1-11/16" |

| SPECIFICATION | PRODUCT RATING |
|------------------|--|
| UL 10C (2009) | 20 Minute-without Hose Stream |
| NFPA 252 (2008) | Positive Pressure |
| NFPA 252 (2012) | Category A- No Additional Edge Sealing |
| CAN4 S104 (1985) | Required |

TEST REPORT

Intertek Test Report No: 3033943, 3084465, 3176111MID-002, 3187023MID-002, 100354358MID-001 & 101083967MID-001

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com

NOPC-03/30/2023