## **NOTICE OF PRODUCT CERTIFICATION**



CERTIFICATION NO:
DATE:
<b>CERTIFICATION PROGRAM:</b>
COMPANY:
CODE:
<b>EXPIRATION DATE:</b>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

PRODUCT DESCRIPTION
Jeld Wen 20 Minute Neutral
Pressure Steel Side-Hinged Door
Assembly
Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
1/2" Minimum Latch Throw Single Swing Only
Single Swing Maximum Size: 3'6" x 6'8" Minimum Thickness: 1-3/4"

## **SPECIFICATION**

NFPA 252 (2008) UL 10B (2009)

UBC 7-2 (1994)

**PRODUCT RATING** 

**20 Minute-Neutral Pressure** With Hose Stream **Category B - Additional Edge Sealing** Required

## **TEST REPORT**

Intertek Test Report No: WHI 495-0897, 100108677COQ-001, 100211525COQ-001, 100237214MID-001, 100754937MID-001 NAMI Waiver of Retest: W-2090

Administrator's Signature:

## NATIONAL ACCREDITATION AND **MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com

NOPC-03/30/2023