NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO:	<u>NI015908</u>
DATE:	11/16/2023
CERTIFICATION PROGRAM:	<u>Fire</u>
COMPANY:	Vision Door
CODE:	2822-1
EXPIRATION DATE:	11/30/2027

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Vision Door & Millwork, LLC	20-90 Minute Foam-Filled Steel Fire Door
2525 Pio Nono Avenue	(Hollow Metal/24 or 26 Gauge/Flush or Embossed)
Macon, GA 31206	Manufacturer Specific Fire Doors for Single or Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single or Double Swing Only
	Maximum Size: 6'0" x 8'0" (Must refer to listing for size/rating limitations) Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (2012)	90 Minute-Positive Pressure
UL 10C (2009/2016)	Without Hose Stream
UL 10B (2009)	20 Minute-Positive Pressure
UBC Standard 7-2 (1994/1997)	With Hose Stream
CAN/ULC S104 (2010/2015)	(26 Gauge Skin - 3'0" x 7'0" Maximum Size)
	Category B - Additional Edge-Sealing
	System Required

TEST REPORT

Intertek EEV No: 100754937MID-001, 100108677COQ-001, 100211525COQ-001 NAMI Waiver of Retest: W-1998/W-2028/W-2063/W-2090

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com

NOPC-03/30/2023