NOTICE OF PRODUCT CERTIFICATION



This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Harbin Lumber Company	"Warm Springs 90-Minute"
660 Smith Road	Flush Panel Composite Fire Doors
Lavonia, GA 30553	Manufacturer Specific Fire Doors for Single or Double Swing Installation in 90 Minute Locations
	1/2" Minimum Latch Throw Single or Double Swing Only
	Maximum Size: 8'0" x 8'0" (Must refer to listing for size/rating limitations) Minimum Thickness: 1-11/16"

SPECIFICATION

NFPA 252 (2012/2017) UL 10C (2009/2016) CAN/ULC S104 (2010/2015) **PRODUCT RATING**

90 Minute-Positive Pressure With Hose Stream Category A - No Additional Edge-Sealing System Required Temperature Rise @ 30 Min: 250° F Max (Where lites do not exceed 100 in²)

TEST REPORT

Intertek Test Report No: 104142512COQ-006 NAMI Waiver of Retest: W-1985/W-1989/W-1998/W-2028

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com

NOPC 03/30/2023