## NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI015939

DATE:  $\frac{12}{12}$ 

**CERTIFICATION PROGRAM:** Fire

**COMPANY:** Harbin Lumber

**CODE:** 2341-1

**EXPIRATION DATE:** 12/31/2027

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Harbin Lumber Company	
660 Smith Road	Routed Particleboard Fire Door
Lavonia, GA 30553	Manufacturer Specific Fire Doors for Single Swing Installation in 20-Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	20-Minute Single Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (2012) UL 10C (2009)	20 Minute-Positive Pressure Without Hose Stream Category B - Additional Edge-Sealing System Required

## **TEST REPORT**

Intertek Test Report No: 3107376COQ-004, 3169105, 3043898, 102245905, 104375792

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com

NOPC 03/30/2023