NOTICE OF PRODUCT CERTIFICATION



NI015994	
02/12/2024	
Fire	
Builders First	
1665-1	
05/31/2027	

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

eve's & Sons/Crest Doors ush or 6-Panel Steel Skin
ush or 6 Panal Staal Skin
usii vi v-i anci steel skili
le-Hinged Door Assembly
r Specific Fire Doors for Single & Double Swing Installation in 20 Minute Locations
1/2" Minimum Latch Throw Single Swing Only
gle Maximum Size: 3'0" x 6'8" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
UL 10C (2021)	20 Minute-Positive Pressure w/o Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 105287053MID-004R1

Administrator's Signature: -

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com

NOPC 03/30/2023