NOTICE OF PRODUCT CERTIFICATION



This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

PRODUCT DESCRIPTION
TruTech Single Swing
Fiberglass Foam Core
Side Hinged Door
Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations
1/2" Minimum Latch Throw Single Swing Only
Maximum Size: 35.75" x 79.06" Minimum Thickness: 1.75"

SPECIFICATIONPRODUCT RATINGUL 10C (2016)20 Minute-Positive Pressure
Without Hose Stream
Category B Door-Additional Edge Seal
Required
For Use in Category C Frame

(or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT

QAI Test Report No: T1172-4

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com

NOPC 03/30/2024