## NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO: NI016100** 

**DATE:** 03/12/2024

**CERTIFICATION PROGRAM:** Fire

Bari Millwork

COMPANY: CODE:

3020-1

**EXPIRATION DATE:** 

03/31/2028

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="https://www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Bari Millwork & Supply, LLC	20 Minute Positive Pressure
1975 Northwest 18th Street	Molded Simulated Panel Side-Hinged
Pompano Beach, FL 33069	Side-Hinged Door Assembly
	Manufacturer Specific Fire Doors for Single Swing or Standard Pairs Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing or Standard Pairs Only
	Single Swing Maximum Size: 3'0" x 8'0" Standard Pairs Maximum Size: 6'0" x 8'0" Minimum Thickness: 1-3/4"

SPECIFICATION	PRODUCT RATING
NFPA 252 (1999)	20 Minute-Positive Pressure
UL 10(b) (2009)	With Hose Stream
CAN4-S104 (1985)(2010)	Category B Door-Additional Edge Seal
UL 10(c) (2009)	Required
	For Use in Category C Frame
	(or may also be installed in Category C-Proprietary in accordance
	with individual manufacturer's listing)

## **TEST REPORT**

Intertek Test Report No: 3192291COQ-005, 100211525COQ-001, 100553244COQ-002, 100581395MID-001, 101432263COQ



Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072

Tel: (804) 684-5124 nami@namiinc.com

NOPC-03/30/2023