NOTICE OF PRODUCT CERTIFICATION



This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com</u>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Monterey Bay Door, Inc.	"ABS 20-Minute"
755 Vertin Avenue, Suite F	Routed Particleboard Fire Door
Salinas, CA 93901	Manufacturer Specific Fire Doors for Single Swing Installation in 20-Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	20-Minute Single Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"
SPECIFICATION	PRODUCT RATING

SPECIFICATIONPRODUCT RATINGNFPA 252 (2012)20 Minute-Positive PressureUL 10C (2009)Without Hose StreamCategory B - Additional Edge-Sealing
System Required

TEST REPORT

Intertek Test Report No: 3107376COQ-004, 3169105, 3043898, 102245905, 104375792

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com

NOPC 03/30/2023