NOTICE OF PRODUCT CERTIFICATION



| CERTIFICATION NO: | N |
|-------------------------------|----------|
| DATE: | <u>0</u> |
| CERTIFICATION PROGRAM: | F |
| COMPANY: | E |
| CODE: | <u>3</u> |
| EXPIRATION DATE: | <u>0</u> |
| | |

| NI016157 | |
|---------------|--|
| 04/29/2024 | |
| Fire | |
| ESI Interiors | |
| 3037-1 | |
| 04/30/2028 | |

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <u>www.namicertification.com.</u> NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION |
|---------------------------|--|
| ESI Interiors Corporation | 20 Minute Positive & Neutral Pressure |
| 12336 West Overland Drive | Flush or Molded Interior Side-Hinged |
| Boise, ID 83709 | Door w/Particleboard Core |
| | Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations |
| | 1/2" Minimum Latch Throw Single Swing Only |
| | Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4" |

SPECIFICATION

NFPA 252 (1999) UL 10(b) (2009) ASTM E2074 (2000) CAN4-S104(ULC S104) UBC Standard 7-2 (1994/1997) UL 10(c) (1998) PRODUCT RATING

20 Minute-Neutral/Positive Pressure With Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT

Intertek Test Report No: 3137713COQ-007

Administrator's Signature:

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com

NOPC 03/30/2023