## NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO:** NI016166

**DATE:** 04/29/2024

CERTIFICATION PROGRAM: Fire

COMPANY: SOCO Door

**CODE:** <u>3050-1</u>

NOPC 03/30/2023

**EXPIRATION DATE: 04/30/2028** 

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="https://www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION	
Soco Door & Window Services, LLC.	<b>Crest Doors 20 Minute Positive Pressure</b>	
2928 North 35th Ave, Suite 4	Particleboard Core/Wood Veneer	
Phoenix, AZ 85017	Side-Hinged Door Assembly	
	Manufacturer Specific Fire Doors for Single & Double Swing Installation in 20 Minute Locations	
	1/2" Minimum Latch Throw Single & Double Swing Only	
	Single Maximum Size: 4'0" x 9'0" Double Maximum Size: 8'0" x 9'0" Minimum Thickness: 1-3/4"	

SPECIFICATION	PRODUCT RATING
UBC-7-2-97 UL 10C (1998)(2009) NFPA 252 (1995)(2008)	20 Minute-Positive Pressure w/o Hose Stream Category A Door-No Additional Edge Seal Required Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT	
Warnock Hershey Test Report No: WHI-495-1367	

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com