## NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO:** NI016168

**DATE:** 04/29/2024

CERTIFICATION PROGRAM: Fire

**COMPANY: SOCO Door** 

**CODE:** <u>3050-1</u>

**EXPIRATION DATE: 04/30/2028** 

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION  20 Minute Positive Pressure		
Soco Door & Window Services, LLC.			
2928 North 35th Ave, Suite 4	Flush or Molded Interior Side-Hinged		
Phoenix, AZ 85017	Door w/Wheatboard Core		
	Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations		
	1/2" Minimum Latch Throw Single Swing Only		
	Maximum Size: 3'0" x 8'0" Minimum Thickness: 1-3/4"		

SPECIFICATION	PRODUCT RATING		
NFPA 252 (1999) UL 10(b) (1997/2009) CAN4-S104 (1985) UBC Standard 7-2 (1994/1997) UL 10(c) (2009)	20 Minute-Positive Pressure With Hose Stream Category B Door-Additional Edge Seal Required For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)		

TEST	$\mathbf{R}\mathbf{F}$	'PA	RT

Intertek Test Report No: 3137714COQ-008

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124

nami@namiinc.com

NOPC 03/30/2023