## **NOTICE OF PRODUCT CERTIFICATION**



CERTIFICATION NO:
DATE:
<b>CERTIFICATION PROGRAM:</b>
<b>COMPANY:</b>
CODE:
<b>EXPIRATION DATE:</b>

FIGHTION

NI016170	
04/29/2024	
Fire	
SOCO Door	
3050-1	
04/30/2028	

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Soco Door & Window Services, LLC.	Steve's & Sons/Crest Doors
2928 North 35th Ave, Suite 4	Flush or 6-Panel Steel Skin
Phoenix, AZ 85017	Side-Hinged Door Assembly
	Manufacturer Specific Fire Doors for Single & Double Swing Installation in 20 Minute Locations
	1/2" Minimum Latch Throw Single Swing Only
	Single Maximum Size: 3'0" x 6'8" Minimum Thickness: 1-3/4"
SPECIFICATION	PRODUCT RATING

SPECIFICATION	PRODUCT RATING
UL 10C (2021)	20 Minute-Positive Pressure w/o Hose Stream Category B Door-Additional Edge Seal Required
	For Use in Category C Frame (or may also be installed in Category C-Proprietary in accordance with
	individual manufacturer's listing)

## **TEST REPORT**

Intertek Test Report No: 105287053MID-004R1

Administrator's Signature:

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway

Hayes, VA 23072 Tel: (804) 684-5124 nami@namiinc.com

NOPC 03/30/2023