

# NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI016412  
DATE: 11/25/2024  
CERTIFICATION PROGRAM: Fire  
COMPANY: Alvey Lumber  
CODE: 2984-1  
EXPIRATION DATE: 11/30/2028

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<b>Alvey Lumber Door Components, LLC</b> <b>401 West 370 South</b> <b>Monroe, UT 84754</b>	<b>20 Minute Positive &amp; Neutral Pressure</b> <b>Flush or Molded Interior Side-Hinged</b> <b>Door w/Particleboard Core</b>  Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations  1/2" Minimum Latch Throw Single Swing Only  <b>Maximum Size: 3'0" x 8'0"</b> <b>Minimum Thickness: 1-3/4"</b>

SPECIFICATION	PRODUCT RATING
<b>NFPA 252 (1999)</b> <b>UL 10(b) (2009)</b> <b>ASTM E2074 (2000)</b> <b>CAN4-S104(ULC S104)</b> <b>UBC Standard 7-2 (1994/1997)</b> <b>UL 10(c) (1998)</b>	<b>20 Minute-Neutral/Positive Pressure</b> <b>With Hose Stream</b> <b>Category B Door-Additional Edge Seal</b> <b>Required</b> <b>For Use in Category C Frame</b> (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT
<b>Intertek Test Report No: 3137713COQ-007</b>

Administrator's Signature: \_\_\_\_\_

A handwritten signature in black ink, appearing to be "S. D.", written over a horizontal line.

**NATIONAL ACCREDITATION AND  
MANAGEMENT INSTITUTE, INC.**

4794 George Washington Memorial Highway

Hayes, VA 23072

Tel: (804) 684-5124

[nami@namiinc.com](mailto:nami@namiinc.com)

NOPC 03/30/2023