NOTICE OF PRODUCT CERTIFICATION

CERTIFICATION NO:	**NI016866-R1**
DATE:	**12/16/2025**
CERTIFICATION PROGRAM:	**Fire**
COMPANY:	**Boise Cascade**
CODE:	**2820-1**
EXPIRATION DATE:	**12/31/2029**
REVISION DATE:	**06/18/2026**

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
Boise Cascade **1020 West 3265 Street** **Salt Lake City, UT 84119**	**20 Minute Positive & Neutral Pressure** **Flush or Molded Interior Side-Hinged** **Door w/Particleboard Core** Manufacturer Specific Fire Doors for Single Swing Installation in 20 Minute Locations 1/2" Minimum Latch Throw Single Swing Only **Maximum Size: 3'0" x 8'0"** **Minimum Thickness: 1-3/4"**

SPECIFICATION	PRODUCT RATING
NFPA 252 (1999) **UL 10(b) (2009)** **ASTM E2074 (2000)** **CAN4-S104(ULC S104)** **UBC Standard 7-2 (1994/1997)** **UL 10(c) (1998)**	**20 Minute-Neutral/Positive Pressure With Hose Stream** **Category B Door-Additional Edge Seal Required** **For Use in Category C Frame** (or may also be installed in Category C-Proprietary in accordance with individual manufacturer's listing)

TEST REPORT
Intertek Test Report No: 3137713COQ-007

Administrator's Signature: _____

NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.
4794 George Washington Memorial Highway
Hayes, VA 23072
Tel: (804) 684-5124
nami@namiinc.com